


Technical Specification

Project name :	Airovision Builder version: E1.13 (12-4-2022)(R086)/A
Quotation no. : 6.1 AHU Technical Guide / 018	Eurovent identification number: 08.02.251
Eurovent identification number: 08.02.251	

GENERAL DATA

Customer reference	6.1.1 15000 11.08
Number off	1
Location	External (flat roof)
Delivery	In sections
AHU finish	Outside in standard colour (RAL 7035)
Product	Air handling unit
AHU configuration	Inline
Pallet option	Excluded
Lifting Beam	Included
Total weight (each)	kg 1069
(Radiated casework SWL)	dB(A) 61
ErP identification code	NRVU / UVU

Eurovent energy classification



Calculations conform to the Regulation for unidirectional ventilation unit (UVU) for delivery after 01.01.2018

Ecodesign 1253/2014 2018 UVU after 01.01.2018

Intermediate calculations

SFP int_limit (W/(m³/s))	230.0
SFP int (W/(m³/s))	116.5
n fan_limit (%)	52.0

Supply air unit data

Airflow (m³/s)	4.17
Static pressure (Pa)	774
p fan (kW)	5.00
n fan (%)	64.5
Fine Filter	Yes
dp Fine filter (Pa)	75

Check

Fan is selected with VSD	Passed
n fan_limit	Passed
SFP int	Passed
Filters equipped with pressure gauge	Passed
Total check	Passed

ACCESS DATA

Handle type	L-Handle	Pressure guard at positive pressure doors	Included
-------------	----------	---	----------

Technical Specification

Project name :	Airovision Builder version: E1.13 (12-4-2022)(R086)/A
Quotation no. : 6.1 AHU Technical Guide / 018	Eurovent identification number: 08.02.251
Eurovent identification number: 08.02.251	

SUPPLY DATA

Glasswool 23 kg/m ³ Type	39HQ 11.08	Air volume	m ³ /s	4.17
Casing construction	GP080 60 mm	Internal sheet		Galvanised 0.80mm
Design outdoor temperature	°C 9.0	External sheet		PUR-PA painted galvanized steel 0.80mm
Design outdoor temperature (summer)	°C 37.5	Insulation		Glasswool 23 kg/m ³
Design outdoor dew point (summer)	°C 16.8	Profile		Steel
Unit velocity	m/s 1.95	SFPv		
SFPe	kJ/m ³ 1.20		kJ/m ³	1.06

Mechanical performance according EN1886

Model box	D1	L1 (-400Pa)	L1 (+400Pa)	L1 (+700Pa)	F9	T2	TB2
Real Unit		L2 (-400Pa)	L2 (+400Pa)	L2 (+700Pa)			

(Sound data supply SWL)	Hz	125	250	500	1k	2k	4k	8k	dB(A)
	dB	58	61	62	60	56	46	37	64
	dB	60	62	63	61	57	47	38	65
	dB	63	66	74	79	76	75	67	82

In direction of airflow, the unit comprises:

DELIVERY SECTION(S)

Section	Width (mm)	Height (mm)	Length (mm)	Baseframe (mm)	Weight (kg)	Weight (Lifting Beam) (kg)
1	1858	1378	3298	62	775	24
2	1858	1378	98	62	39	
3	1858	1378	898	62	254	

EXHAUST COMPONENTS

SUPPLY COMPONENTS

Technical Specification

Project name :	Airovision Builder version: E1.13 (12-4-2022)(R086)/A
Quotation no. : 6.1 AHU Technical Guide / 018	Eurovent identification number: 08.02.251
Eurovent identification number: 08.02.251	

SINGLE MIXING BOX				
Opening Position		Top	Provided with:	
Number of Recirc openings		1	Opening product	None
Recirc opening, w x h	mm	1760 x 480	Damper	External, Opposed blades, Aluminium
Pressure drop	Pa	28	Number of Dampers	1
Actuator type		External	Damper Code	DMP1658x0378-200-162-2-D1Y2-0
Actuator Side		Left	Number of Drive shafts (Total) x Torque for one shaft	Nm 1 x 5
Access side		None	Provided with:	
Opening Position		Full face	Opening product	None
Number of openings		1	Damper	External, Opposed blades, Aluminium
Fresh air opening, w x h	mm	1760 x 1280	Number of Dampers	1
Pressure drop	Pa	3	Damper Code	DMP1658x1178-200-162-7-D1Y2-0
Actuator type		External	Number of Drive shafts (Total) x Torque for one shaft	Nm 1 x 12
Actuator Side		Left	Mixing ratio, winter (recirculation air/supply air) in %	0
Access side		None		

EXTRAS

1 x Coupling rod for dampers

COMBINED FILTER				
Primary filter type		Panel (Synthetic)	Secondary filter type	Bag (Synthetic)
Test method		EN 779 / ISO 16890	Test method	EN 779 / ISO 16890
EN 779 Class		G4	EN 779 Class	F7
Eurovent Efficiency Class		NA	Eurovent Efficiency Class	E
ISO 16890 Class		ISO Coarse 60	ISO 16890 Class	ISO ePM1 50
Design pressure drop		Mean pd	Design pressure drop	Mean pd
Initial pressure drop	Pa	62	Initial pressure drop	Pa 79
Mean pressure drop	Pa	87	Mean pressure drop	Pa 129
Final pressure drop	Pa	112	Final pressure drop	Pa 179
Filter casing material		Galvanised	Filter casing material	Galvanised
Filter frame material		Galvanised	Withdrawal method	Side
Filter length	mm	48	Filter length	mm 500
Filters			Filters	
592x592	Qty	4	592x592	Qty 4
437x592	Qty	2	437x592	Qty 2
ACCESS			ACCESS	
Access type		Door	Access side	Right

EXTRAS

2 x Pressure gauge wall mounted, Magnehelic 2000

Technical Specification

Project name :	Airovision Builder version: E1.13 (12-4-2022)(R086)/A
Quotation no. : 6.1 AHU Technical Guide / 018	Eurovent identification number: 08.02.251
Eurovent identification number: 08.02.251	

CHILLED WATER COIL			Number of coils		1
Coil Code	P25-10AR-5R-46T-1533A-2.0PA-38NC-Cu	0.36/Al 0.10-2 1/2"			
Air volume	m ³ /s	4.17	Fluid	100%	Water
Duty	kW	94.16	Fluid flow rate	l/s	4.48
Air on db	°C	27.0	Fluid on	°C	7.0
Air on wb/RH	°C/%	19.0/47	Fluid off	°C	12.0
Air off db	°C	13.0	Fluid content	l	35.14
Air off wb/RH	°C/%	12.4/94	Fluid pressure drop	kPa	48
Sensible duty	kW	70.00			
Air pressure drop coil (Dry)	Pa	92	Air pressure drop elim.	Pa	13
Tubes/fins/connections		Cu / Al / Fe	Connection type		Threaded (Right)
Coil frame		Galvanised	Connection size		2 1/2"
Tube thickness	mm	0.36	Fin spacing	mm	2.0
Tube Diameter	mm	9.2388	Fin thickness	mm	0.10
Face velocity	m/s	2.3			
Eliminator		Plastic – side withdrawal	Eliminator frame		Galvanised
Drainpan type		Recessed (sloped)	Drainpan material		Stainless steel 304
Drain pipes on drainpan		1	Intermediate drainpan		No
Condensed Water	l/min	0.5	Syphon Type		Negative
Coil Weight	kg	101.51	Xin/Yin/Xout/Yout	mm/mm/ mm/mm	177/71/89/89

EXTRAS
1 x Syphone

HOT WATER COIL			Number of coils		1
Coil Code	P25-10AR-2R-46T-1533A-2.0PA-32NC-Cu	0.36/Al 0.10-2 1/2"			
Air volume	m ³ /s	4.17	Fluid	100%	Water
Duty	kW	85.00	Fluid flow rate	l/s	4.11
Air on db	°C	8.0	Fluid on	°C	45.0
Air off db	°C	25.0	Fluid off	°C	40.0
Air pressure drop	Pa	30	Fluid content	l	20.21
			Fluid pressure drop	kPa	16
Tubes/fins/connections		Cu / Al / Fe	Connection type		Threaded (Right)
Coil frame		Galvanised	Connection size		2 1/2"
Tube thickness	mm	0.36	Fin spacing	mm	2.0
Tube Diameter	mm	9.2388	Fin thickness	mm	0.10
Face velocity	m/s	2.3	Xin/Yin/Xout/Yout	mm/mm/ mm/mm	175/71/89/89
Coil Weight	kg	59.94			

EXTRAS
1 x Syphone

Technical Specification

Project name :	Airovision Builder version: E1.13 (12-4-2022)(R086)/A
Quotation no. : 6.1 AHU Technical Guide / 018	Eurovent identification number: 08.02.251
Eurovent identification number: 08.02.251	

STEAM HUMIDIFIER					
Air volume	m ³ /s	4.17	Humidifier supplier		Condair
Moisture addition	kg/h	70	Number of steam lances		2
Air on db	°C	25.0	Steam lance length	mm	1500
Air on moisture content	g/kg	2.8			
Air on rh	%	32			
Air off db	°C	25.7			
Air off moisture content	g/kg	6.6			
Air off rh	%	32			
Steam boiler type 1		EL70	Power each	kW	2 x 26.3
Max steam capacity, each	kg/h	70	Current each	A	2 x 37.9
Number off		1	Voltage	V	3x400V, 50/60Hz
Boiler weight, each	kg	80			
Section length	mm	960	Drainpan material		Stainless steel 304
Drainpan		Included			

Note: Electric boilers will be delivered separately (not mounted on the unit). Boiler weights not included in unit weights.

ACCESS			
Access type	Door	Access side	Right

EXTRAS
1 x Syphone

ANY COMPONENT		
Pressure drop	Pa	0

INLET PLENUM		
Air pressure drop	Pa	0

ACCESS			
Access type	Door	Access side	Right

FAN									
Fan type		K3G400PI9205							
Fan arrangement		Fan Wall - 2B1							
Air volume	m ³ /s	3 x 1.39		Installed motor power	kW	2.50			
External static pressure	Pa	392		Motor		Run			
Internal static pressure	Pa	378		Motor efficiency class		IE4			
Static pressure ISP+ESP	Pa	770		Motor nominal speed	rpm	2450			
System effect	Pa	4		Voltage	V	380-480			
Extra static pressure	Pa	0		Current	A	3.8			
Total static pressure	Pa	774		Abs. motor power incl. F.I.	kW	1.67			
Dynamic pressure	Pa	38		Control Signal (0-10V)	V	7.24			
Total pressure	Pa	813		Fan bulkhead material		Galvanised			
Fan speed	rpm	2140							
Max fan speed	rpm	2450							
Efficiency (total)	%	67							
Fan shaft power	kW	1.67							
(Fan sound data SWL)	Hz	63	125	250	500	1k	2k	4k	8k
Total	Inlet dB	41	63	66	68	72	71	71	62
	Outlet dB	44	63	66	74	79	76	75	67

FAN EXTRAS
Inlet cone measuring points

