


Technical Specification

Project name :	Airovision Builder version: E1.13 (12-4-2022)(R086)/A
Quotation no. : 6.1 AHU Technical Guide / 035	Eurovent identification number: 08.02.251
Eurovent identification number: 08.02.251	

GENERAL DATA

Customer reference	6.1.1 40000 21.10
Number off	1
Location	External (flat roof)
Delivery	In sections
AHU finish	Outside in standard colour (RAL 7035)
Product	Air handling unit
AHU configuration	Inline
Pallet option	Included
Lifting Beam	Included
Total weight (each)	kg 2484
(Radiated casework SWL)	dB(A) 73
ErP identification code	NRVU / UVU

Eurovent energy classification



Calculations conform to the Regulation for unidirectional ventilation unit (UVU) for delivery after 01.01.2018

Ecodesign 1253/2014 2018 UVU after 01.01.2018

Intermediate calculations

SFP int_limit (W/(m³/s))	230.0
SFP int (W/(m³/s))	132.1
n fan_limit (%)	58.5

Supply air unit data

Airflow (m³/s)	11.11
Static pressure (Pa)	806
p fan (kW)	14.35
n fan (%)	62.4
Fine Filter	Yes
dp Fine filter (Pa)	82

Check

Fan is selected with VSD	Passed
n fan_limit	Passed
SFP int	Passed
Filters equipped with pressure gauge	Passed
Total check	Passed

ACCESS DATA

Handle type	L-Handle	Pressure guard at positive pressure doors	Included
-------------	----------	---	----------

Technical Specification

Project name :	Airovision Builder version: E1.13 (12-4-2022)(R086)/A
Quotation no. : 6.1 AHU Technical Guide / 035	Eurovent identification number: 08.02.251
Eurovent identification number: 08.02.251	

SUPPLY DATA

Glasswool 23 kg/m ³ Type	39HQ 21.10	Air volume	m ³ /s	11.11
Casing construction	GP080 60 mm	Internal sheet		Galvanised 0.80mm
Design outdoor temperature	°C 9.0	External sheet		PUR-PA painted galvanized steel 0.80mm
Design outdoor temperature (summer)	°C 37.5	Insulation		Glasswool 23 kg/m ³
Design outdoor dew point (summer)	°C 16.8	Profile		Steel
Unit velocity	m/s 2.15	SFPv		
SFPe	kJ/m ³ 1.29		kJ/m ³	1.23

Mechanical performance according EN1886	Model box	D1	L1 (-400Pa)	L1 (+400Pa)	L1 (+700Pa)	F9	T2	TB2
	Real Unit		L2 (-400Pa)	L2 (+400Pa)	L2 (+700Pa)			

(Sound data supply SWL)	Hz	125	250	500	1k	2k	4k	8k	dB(A)
	dB	57	67	68	65	63	56	55	70
	dB	67	70	71	69	65	57	55	73
	dB	64	74	79	93	85	84	81	94

In direction of airflow, the unit comprises:

DELIVERY SECTION(S)

Section	Width (mm)	Height (mm)	Length (mm)	Baseframe (mm)	Weight (kg)	Weight (Lifting Beam) (kg)
1	3458	1698	2338	62	1400	30
2	3458	1698	1058	62	304	
3	3458	1698	98	62	67	
4	3458	1698	898	62	711	

EXHAUST COMPONENTS

SUPPLY COMPONENTS

Technical Specification

Project name :	Airovision Builder version: E1.13 (12-4-2022)(R086)/A
Quotation no. : 6.1 AHU Technical Guide / 035	Eurovent identification number: 08.02.251
Eurovent identification number: 08.02.251	

SINGLE MIXING BOX

Opening Position		Top	Provided with:	
Number of Recirc openings		1	Opening product	None
Recirc opening, w x h	mm	3360 x 480	Damper	External, Opposed blades, Aluminium
Pressure drop	Pa	51	Number of Dampers	1
Actuator type		External	Damper Code	DMP3258x0378-200-162-2-D1Y2-0
Actuator Side		Left	Number of Drive shafts (Total) x Torque for one shaft	Nm 1 x 5
Access side		None	Provided with:	
Opening Position		Full face	Opening product	None
Number of openings		1	Damper	External, Opposed blades, Aluminium
Fresh air opening, w x h	mm	3360 x 1600	Number of Dampers	1
Pressure drop	Pa	3	Damper Code	DMP3258x1498-200-162-9-D1Y2-0
Actuator type		External	Number of Drive shafts (Total) x Torque for one shaft	Nm 1 x 15
Actuator Side		Left	Mixing ratio, winter (recirculation air/supply air) in %	0
Access side		None		

EXTRAS

1 x Coupling rod for dampers

COMBINED FILTER

Primary filter type		Panel (Synthetic)	Secondary filter type		Bag (Synthetic)
Test method		EN 779 / ISO 16890	Test method		EN 779 / ISO 16890
EN 779 Class		G4	EN 779 Class		F7
Eurovent Efficiency Class		NA	Eurovent Efficiency Class		E
ISO 16890 Class		ISO Coarse 60	ISO 16890 Class		ISO ePM1 50
Design pressure drop		Mean pd	Design pressure drop		Mean pd
Initial pressure drop	Pa	67	Initial pressure drop	Pa	87
Mean pressure drop	Pa	92	Mean pressure drop	Pa	137
Final pressure drop	Pa	117	Final pressure drop	Pa	187
Filter casing material		Galvanised	Filter casing material		Galvanised
Filter frame material		Galvanised	Withdrawal method		Side
Filter length	mm	48	Filter length	mm	500
Filters			Filters		
592x592	Qty	10	592x592	Qty	10
592x287	Qty	7	287x592	Qty	2
287x287	Qty	1	592x287	Qty	5
			287x287	Qty	1

ACCESS

Access type	Door	Access side	Right
-------------	------	-------------	-------

EXTRAS

2 x Pressure gauge wall mounted, Magnehelic 2000

Technical Specification

Project name :	Airovision Builder version: E1.13 (12-4-2022)(R086)/A
Quotation no. : 6.1 AHU Technical Guide / 035	Eurovent identification number: 08.02.251
Eurovent identification number: 08.02.251	

CHILLED WATER COIL			Number of coils		1
Coil Code	P40-16AR-5R-37T-3063A-2.0PA-32NC-Cu	0.41/Al 0.13-4"			
Air volume	m ³ /s	11.11	Fluid	100%	Water
Duty	kW	251.09	Fluid flow rate	l/s	11.96
Air on db	°C	27.0	Fluid on	°C	7.0
Air on wb/RH	°C/%	19.0/47	Fluid off	°C	12.0
Air off db	°C	13.0	Fluid content	l	121.93
Air off wb/RH	°C/%	12.4/94	Fluid pressure drop	kPa	47
Sensible duty	kW	186.67			
Air pressure drop coil (Dry)	Pa	99	Air pressure drop elim.	Pa	14
Tubes/fins/connections		Cu / Al / Fe	Connection type		Threaded (Right)
Coil frame		Galvanised	Connection size		4"
Tube thickness	mm	0.41	Fin spacing	mm	2.0
Tube Diameter	mm	14.1872	Fin thickness	mm	0.13
Face velocity	m/s	2.4			
Eliminator		Plastic – side withdrawal	Eliminator frame		Galvanised
Drainpan type		Recessed (sloped)	Drainpan material		Stainless steel 304
Drain pipes on drainpan		1	Intermediate drainpan		No
Condensed Water	l/min	1.4	Syphon Type		Negative
Coil Weight	kg	367.54	Xin/Yin/Xout/Yout	mm/mm/ mm/mm	244/110/106/106

EXTRAS
1 x Syphone

HOT WATER COIL			Number of coils		1
Coil Code	P40-16AR-2R-37T-3063A-2.0PA-27NC-Cu	0.41/Al 0.13-4"			
Air volume	m ³ /s	11.11	Fluid	100%	Water
Duty	kW	213.33	Fluid flow rate	l/s	10.31
Air on db	°C	8.0	Fluid on	°C	45.0
Air off db	°C	24.0	Fluid off	°C	40.0
Air pressure drop	Pa	33	Fluid content	l	66.25
			Fluid pressure drop	kPa	16
Tubes/fins/connections		Cu / Al / Fe	Connection type		Threaded (Right)
Coil frame		Galvanised	Connection size		4"
Tube thickness	mm	0.41	Fin spacing	mm	2.0
Tube Diameter	mm	14.1872	Fin thickness	mm	0.13
Face velocity	m/s	2.4	Xin/Yin/Xout/Yout	mm/mm/ mm/mm	250/110/100/100
Coil Weight	kg	202.39			

EXTRAS
1 x Syphone

Technical Specification

Project name :	Airovision Builder version: E1.13 (12-4-2022)(R086)/A
Quotation no. : 6.1 AHU Technical Guide / 035	Eurovent identification number: 08.02.251
Eurovent identification number: 08.02.251	

STEAM HUMIDIFIER					
Air volume	m ³ /s	11.11	Humidifier supplier		Condair
Moisture addition	kg/h	186	Number of steam lances		5
Air on db	°C	25.0	Steam lance length	mm	2500
Air on moisture content	g/kg	2.8			
Air on rh	%	32			
Air off db	°C	25.7			
Air off moisture content	g/kg	6.6			
Air off rh	%	32			
Steam boiler type 1		EL120	Power each	kW	3 x 30.0
Max steam capacity, each	kg/h	120	Current each	A	3 x 43.3
Number off		1	Voltage	V	3x400V, 50/60Hz
Boiler weight, each	kg	120			
Steam boiler type 2		EL90	Power each	kW	2 x 33.8
Max steam capacity, each	kg/h	90	Current each	A	2 x 48.7
Number off		1	Voltage	V	3x400V, 50/60Hz
Boiler weight, each	kg	80			
Section length	mm	960	Drainpan material		Stainless steel 304
Drainpan		Included			

Note: Electric boilers will be delivered separately (not mounted on the unit). Boiler weights not included in unit weights.

ACCESS			
Access type	Door	Access side	Right

EXTRAS
1 x Syphone

ANY COMPONENT		
Pressure drop	Pa	0

INLET PLENUM		
Air pressure drop	Pa	0

ACCESS			
Access type	Door	Access side	Right

FAN					
Fan type		K3G450PB2405			
Fan arrangement		Fan Wall - 1x4			
Air volume	m ³ /s	4 x 2.78			
External static pressure	Pa	392			
Internal static pressure	Pa	404			
Static pressure ISP+ESP	Pa	796			
System effect	Pa	10			
Extra static pressure	Pa	0			
Total static pressure	Pa	806			
Dynamic pressure	Pa	97			
Total pressure	Pa	903			
Fan speed	rpm	2325			
Max fan speed	rpm	2600			
Efficiency (total)	%	69			
Fan shaft power	kW	3.59			
		Installed motor power	kW	5.25	
		Motor		Run	
		Motor efficiency class		IE4	
		Motor nominal speed	rpm	2600	
		Voltage	V	380-480	
		Current	A	8.0	
		Abs. motor power incl. F.I.	kW	3.59	
		Control Signal (0-10V)	V	7.91	
		Fan bulkhead material		Galvanised	

(Fan sound data SWL)	Hz	63	125	250	500	1k	2k	4k	8k
Total	Inlet dB	38	62	72	74	77	78	81	80
	Outlet dB	44	64	74	79	93	85	84	81



Date: 17/6/2022



Technical Specification

Project name :	Airovision Builder version: E1.13 (12-4-2022)(R086)/A
Quotation no. : 6.1 AHU Technical Guide / 035	Eurovent identification number: 08.02.251
Eurovent identification number: 08.02.251	

FAN EXTRAS
Inlet cone measuring points

ACCESS			
Access type	Door	Access side	Right

EXTRAS	
2 x Measuring nipple, 6mm	4 x Fanwall terminal box

OUTLET			
Opening Position		Full face	Provided with:
Number of openings		1	Opening product
Opening, width x height	mm	3360 x 1600	Duct spigot
Pressure drop	Pa	2	