



Technical Specification

Project name :	Airovision Builder version: E1.13 (12-4-2022)(R086)/A
Quotation no. : 6.1 AHU Technical Guide / 011	Eurovent identification number: 08.02.251
Eurovent identification number: 08.02.251	

GENERAL DATA

Customer reference	6.1.1 7500 12.04
Number off	1
Location	External (flat roof)
Delivery	In sections
AHU finish	Outside in standard colour (RAL 7035)
Product	Air handling unit
AHU configuration	Inline
Pallet option	Excluded
Lifting Beam	Included
Total weight (each)	kg 768
(Radiated casework SWL)	dB(A) 57
ErP identification code	NRVU / UVU

Eurovent energy classification



Calculations conform to the Regulation for unidirectional ventilation unit (UVU) for delivery after 01.01.2018

Ecodesign 1253/2014 2018 UVU after 01.01.2018

Intermediate calculations

SFP int_limit (W/(m³/s))	230.0
SFP int (W/(m³/s))	109.2
n fan_limit (%)	47.8

Supply air unit data

Airflow (m³/s)	2.08
Static pressure (Pa)	747
p fan (kW)	2.55
n fan (%)	61.0
Fine Filter	Yes
dp Fine filter (Pa)	67

Check

Fan is selected with VSD	Passed
n fan_limit	Passed
SFP int	Passed
Filters equipped with pressure gauge	Passed
Total check	Passed

ACCESS DATA

Handle type	L-Handle	Pressure guard at positive pressure doors	Included
-------------	----------	---	----------

Technical Specification

Project name :	Airovision Builder version: E1.13 (12-4-2022)(R086)/A
Quotation no. : 6.1 AHU Technical Guide / 011	Eurovent identification number: 08.02.251
Eurovent identification number: 08.02.251	

SUPPLY DATA

Glasswool 23 kg/m ³ Type	39HQ 12.04	Air volume	m ³ /s	2.08
Casing construction	GP080 60 mm	Internal sheet		Galvanised 0.80mm
Design outdoor temperature	°C 9.0	External sheet		PUR-PA painted galvanized steel 0.80mm
Design outdoor temperature (summer)	°C 37.5	Insulation		Glasswool 23 kg/m ³
Design outdoor dew point (summer)	°C 16.8	Profile		Steel
Unit velocity	m/s 1.85			
SFP _e	kJ/m ³ 1.23	SFP _v	kJ/m ³	1.08

Mechanical performance according EN1886

Model box	D1	L1 (-400Pa)	L1 (+400Pa)	L1 (+700Pa)	F9	T2	TB2
Real Unit		L2 (-400Pa)	L2 (+400Pa)	L2 (+700Pa)			

(Sound data supply SWL)	Hz	125	250	500	1k	2k	4k	8k	dB(A)
	dB	45	64	63	52	53	43	35	62
	dB	48	64	63	52	53	43	35	62
	dB	49	69	70	72	73	72	64	78

In direction of airflow, the unit comprises:

DELIVERY SECTION(S)

Section	Width (mm)	Height (mm)	Length (mm)	Baseframe (mm)	Weight (kg)	Weight (Lifting Beam) (kg)
1	2018	738	2818	62	538	26
2	2018	738	98	62	36	
3	2018	738	738	62	193	

EXHAUST COMPONENTS

SUPPLY COMPONENTS

Technical Specification

Project name :	Airovision Builder version: E1.13 (12-4-2022)(R086)/A
Quotation no. : 6.1 AHU Technical Guide / 011	Eurovent identification number: 08.02.251
Eurovent identification number: 08.02.251	

SINGLE MIXING BOX

Opening Position		Top	Provided with:		
Number of Recirc openings		1	Opening product		None
Recirc opening, w x h	mm	1920 x 320	Damper		External, Opposed blades, Aluminium
Pressure drop	Pa	14	Number of Dampers		1
Actuator type		External	Damper Code		DMP1838x0238-110-102-2-D1Y2-0
Actuator Side		Left			
Access side		None	Number of Drive shafts (Total) x Torque for one shaft	Nm	1 x 5
Opening Position		Full face	Provided with:		
Number of openings		1	Opening product		None
Fresh air opening, w x h	mm	1920 x 640	Damper		External, Opposed blades, Aluminium
Pressure drop	Pa	3	Number of Dampers		1
Actuator type		External	Damper Code		DMP1838x0558-110-102-6-D1Y2-0
Actuator Side		Left			
Access side		None	Number of Drive shafts (Total) x Torque for one shaft	Nm	1 x 11
Mixing ratio, winter (recirculation air/supply air) in %	%	0			

EXTRAS

1 x Coupling rod for dampers

COMBINED FILTER

Primary filter type		Panel (Synthetic)	Secondary filter type		Bag (Synthetic)
Test method		EN 779 / ISO 16890	Test method		EN 779 / ISO 16890
EN 779 Class		G4	EN 779 Class		F7
Eurovent Efficiency Class		NA	Eurovent Efficiency Class		E
ISO 16890 Class		ISO Coarse 60	ISO 16890 Class		ISO ePM1 50
Design pressure drop		Mean pd	Design pressure drop		Mean pd
Initial pressure drop	Pa	54	Initial pressure drop	Pa	69
Mean pressure drop	Pa	79	Mean pressure drop	Pa	119
Final pressure drop	Pa	104	Final pressure drop	Pa	169
Filter casing material		Galvanised	Filter casing material		Galvanised
Filter frame material		Galvanised	Withdrawal method		Side
Filter length	mm	48	Filter length	mm	500

Filters

592x592	Qty	3	592x592	Qty	3
---------	-----	---	---------	-----	---

ACCESS

Access type	Hatch	Access side	Right
-------------	-------	-------------	-------

EXTRAS

2 x Pressure gauge wall mounted, Magnehelic 2000

Technical Specification

Project name :	Airovision Builder version: E1.13 (12-4-2022)(R086)/A
Quotation no. : 6.1 AHU Technical Guide / 011	Eurovent identification number: 08.02.251
Eurovent identification number: 08.02.251	

CHILLED WATER COIL			Number of coils		1
Coil Code	P25-10AR-5R-22T-1723A-2.0PA-21NC-Cu 0.36/Al 0.10-1 1/2"				
Air volume	m³/s	2.08	Fluid	100%	Water
Duty	kW	47.08	Fluid flow rate	l/s	2.24
Air on db	°C	27.0	Fluid on	°C	7.0
Air on wb/RH	°C/%	19.0/47	Fluid off	°C	12.0
Air off db	°C	13.0	Fluid content	l	15.21
Air off wb/RH	°C/%	12.4/94	Fluid pressure drop	kPa	38
Sensible duty	kW	35.00			
Air pressure drop coil (Dry)	Pa	82	Air pressure drop elim.	Pa	11
Tubes/fins/connections	Cu / Al / Fe		Connection type	Threaded (Right)	
Coil frame	Galvanised		Connection size	1 1/2"	
Tube thickness	mm	0.36	Fin spacing	mm	2.0
Tube Diameter	mm	9.2388	Fin thickness	mm	0.10
Face velocity	m/s	2.1			
Eliminator	Plastic – side withdrawal		Eliminator frame	Galvanised	
Drainpan type	Recessed (sloped)		Drainpan material	Stainless steel 304	
Drain pipes on drainpan	1		Intermediate drainpan	No	
Condensed Water	l/min	0.3	Syphon Type	Negative	
Coil Weight	kg	53.07	Xin/Yin/Xout/Yout	mm/mm/ mm/mm	164/57/76/76

EXTRAS

1 x Syphone

HOT WATER COIL			Number of coils		1
Coil Code	P25-10AR-2R-22T-1723A-2.0PA-17NC-Cu 0.36/Al 0.10-1 1/2"				
Air volume	m³/s	2.08	Fluid	100%	Water
Duty	kW	42.50	Fluid flow rate	l/s	2.05
Air on db	°C	8.0	Fluid on	°C	45.0
Air off db	°C	25.0	Fluid off	°C	40.0
Air pressure drop	Pa	26	Fluid content	l	7.23
			Fluid pressure drop	kPa	16
Tubes/fins/connections	Cu / Al / Fe		Connection type	Threaded (Right)	
Coil frame	Galvanised		Connection size	1 1/2"	
Tube thickness	mm	0.36	Fin spacing	mm	2.0
Tube Diameter	mm	9.2388	Fin thickness	mm	0.10
Face velocity	m/s	2.1	Xin/Yin/Xout/Yout	mm/mm/ mm/mm	143/57/75/75
Coil Weight	kg	29.58			

EXTRAS

1 x Syphone

Technical Specification

Project name :	Airovision Builder version: E1.13 (12-4-2022)(R086)/A
Quotation no. : 6.1 AHU Technical Guide / 011	Eurovent identification number: 08.02.251
Eurovent identification number: 08.02.251	

STEAM HUMIDIFIER					
Air volume	m³/s	2.08	Humidifier supplier		Condair
Moisture addition	kg/h	35	Number of steam lances		1
Air on db	°C	25.0	Steam lance length	mm	1500
Air on moisture content	g/kg	2.8			
Air on rh	%	32			
Air off db	°C	25.7			
Air off moisture content	g/kg	6.6			
Air off rh	%	32			
Steam boiler type 1		EL35	Power each	kW	26.3
Max steam capacity, each	kg/h	35	Current each	A	37.9
Number off		1	Voltage	V	3x400V, 50/60Hz
Boiler weight, each	kg	40			
Section length	mm	960	Drainpan material		Stainless steel 304
Drainpan		Included			

Note: Electric boilers will be delivered separately (not mounted on the unit). Boiler weights not included in unit weights.

ACCESS			
Access type	Hatch	Access side	Right

EXTRAS
1 x Syphone

ANY COMPONENT		
Pressure drop	Pa	0

INLET PLENUM		
Air pressure drop	Pa	0

ACCESS			
Access type	Hatch	Access side	Right

FAN									
Fan type		K3G310PT08J4			Installed motor power	kW	1.23		
Fan arrangement		Fan Wall - 1x3			Motor		Run		
Air volume	m³/s	3 x 0.69			Motor efficiency class		IE4		
External static pressure	Pa	392			Motor nominal speed	rpm	3010		
Internal static pressure	Pa	345			Voltage	V	380-480		
Static pressure ISP+ESP	Pa	737			Current	A	1.9		
System effect	Pa	11			Abs. motor power incl. F.I.	kW	0.85		
Extra static pressure	Pa	0			Control Signal (0-10V)	V	7.47		
Total static pressure	Pa	747			Fan bulkhead material		Galvanised		
Dynamic pressure	Pa	27							
Total pressure	Pa	775							
Fan speed	rpm	2626							
Max fan speed	rpm	3010							
Efficiency (total)	%	62							
Fan shaft power	kW	0.85							
(Fan sound data SWL)	Hz	63	125	250	500	1k	2k	4k	8k
Total	Inlet dB	35	50	69	69	64	68	68	60
	Outlet dB	36	49	69	70	72	73	72	64

FAN EXTRAS
Inlet cone measuring points

Technical Specification

Project name :	Airovision Builder version: E1.13 (12-4-2022)(R086)/A
Quotation no. : 6.1 AHU Technical Guide / 011	Eurovent identification number: 08.02.251
Eurovent identification number: 08.02.251	

ACCESS			
Access type	Hatch	Access side	Right

EXTRAS		
2 x Measuring nipple, 6mm	1 x Fanwall terminal box	

OUTLET			
Opening Position		Full face	
Number of openings		1	
Opening, width x height	mm	1920 x 640	
Pressure drop	Pa	2	
		Provided with:	
		Opening product	Duct spigot